

# Boorbussen Din 172 A

Uitvoering: Gehard, ontlaten, boring  
geslepen.

Beide uiteinden afgerond.

Materiaal: Gehard staal.

Hardheid: 740 + 80 HV 10.



	d1	d2	d3	l			L2	r	tr	tp
	F7	n6		Kort	Middel	Lang				
van 0,4 t/m 1,0	3	6	6	9			2	1		
van 1,1 t/m 1,8	4	7	6	9			2	1		
van 1,9 t/m 2,6	5	8	6	9			2	1		
van 2,7 t/m 3,3	6	9	8	12	16		2,5	1		
van 3,4 t/m 4,0	7	10	8	12	16		2,5	1		
van 4,1 t/m 5,0	8	11	8	12	16		2,5	1	0,01	
van 5,1 t/m 6,0	10	13	10	16	20		3	1,5		
van 6,1 t/m 8,0	12	15	10	16	20		3	1,5		
van 8,1 t/m 10,0	15	18	12	20	25		3	2		
van 10,1 t/m 12,0	18	22	12	20	25		4	2		
van 12,1 t/m 15,0	22	26	16	28	36		4	2		
van 15,1 t/m 18,0	26	30	16	28	36		4	2		
van 18,1 t/m 22,0	30	34	20	36	40		5	3	0,03	
van 22,1 t/m 26,0	35	39	20	36	45		5	3		
van 26,1 t/m 30,0	42	46	25	45	56		5	3		
van 30,1 t/m 35,0	48	52	25	45	56		5	3	0,02	
van 35,1 t/m 42,0	55	59	30	56	67		5	3,5	0,04	0,05

