



Most sizes over 170mm are without lugs										Measurements in mm & M					
Beam #	Crimp Dimensions									Groove Dimensions				Code No.	
	t	Tot	Ø	Tot	Ø _h	h	L	h	F ₁ M8	Ø	Tot	W	s		F ₁ M8
8	0.80	+0.00 -0.50	8.7	+0.30 -0.10	3.0	1.3	2.4	1.0	2.0	8.4	+0.09 -0.00	0.90	0.6	0.86	INT0080
9	0.80		9.8		3.7	1.3	2.6	1.0	2.0	9.4		0.90	0.6	0.96	INT0090
10	1.00	10.0	3.3		1.4	3.2	1.2	4.0	10.4	1.10		0.6	1.06	INT0100	
11	1.00	11.8	4.1		1.5	3.3	1.2	4.0	11.4	1.10		0.8	1.17	INT0110	
12	1.00	13.0	4.8		1.7	3.4	1.5	4.0	12.5	1.10		0.8	1.6	INT0120	
13	1.00	14.1	5.4		1.8	3.6	1.5	4.2	13.6	1.10		0.9	2.1	INT0130	
14	1.00	15.1	6.2		1.9	3.7	1.7	4.5	14.6	1.10		0.9	2.25	INT0140	
15	1.00	16.2	7.2		2.0	3.7	1.7	5.0	15.7	1.10		1.1	2.8	INT0150	
16	1.00	17.3	8.0		2.0	3.8	1.7	5.5	16.8	1.10		1.2	3.4	INT0160	
17	1.00	18.3	8.8		2.1	3.9	1.7	6.0	17.8	1.10		1.2	3.6	INT0170	
18	1.00	19.5	9.4	2.2	4.1	2.0	6.5	19.0	1.10	1.5	4.8	INT0180			
19	1.00	20.5	10.4	2.2	4.1	2.0	6.8	20.0	1.10	1.5	5.1	INT0190			
20	1.00	21.5	11.2	2.2	4.2	2.0	7.2	21.0	1.10	1.5	5.4	INT0200			
21	1.00	22.6	12.2	2.4	4.2	2.0	7.6	22.0	1.10	1.6	5.7	INT0210			
22	1.00	23.5	13.2	2.5	4.2	2.0	8.0	23.0	1.10	1.5	5.9	INT0220			
23	1.20	24.6	14.2	2.5	4.2	2.0	13.8	24.1	1.30	1.5	6.6	INT0230			
24	1.20	25.9	14.8	2.6	4.4	2.0	13.9	25.2	1.30	1.6	7.7	INT0240			
25	1.20	26.9	15.5	2.7	4.5	2.0	14.6	26.2	1.30	1.8	8.0	INT0250			
26	1.20	27.9	16.1	2.8	4.7	2.0	13.95	27.2	1.30	1.8	8.4	INT0260			
27	1.20	29.1	17.1	2.8	4.7	2.0	13.3	28.4	1.30	2.1	10.1	INT0270			
28	1.20	30.1	17.9	2.9	4.8	2.0	13.3	29.4	1.30	2.1	10.5	INT0280			
29	1.20	31.1	18.4	3.0	4.8	2.0	13.6	30.4	1.30	2.1	10.9	INT0290			
30	1.20	32.1	19.9	3.0	4.8	2.0	13.7	31.4	1.30	2.1	11.2	INT0300			
31	1.20	33.4	20.0	3.2	5.2	2.5	13.8	32.7	1.30	2.6	14.1	INT0310			
32	1.20	34.4	20.6	3.2	5.4	2.5	13.0	33.7	1.30	2.6	14.6	INT0320			
33	1.20	35.5	21.8	3.3	5.4	2.5	14.3	34.7	1.30	2.8	15.0	INT0330			
34	1.50	36.5	22.8	3.3	5.4	2.5	26.2	35.7	1.60	2.6	15.4	INT0340			
35	1.50	37.6	23.6	3.4	5.4	2.5	26.9	37.0	1.60	3.0	16.8	INT0350			
36	1.50	38.8	24.6	3.5	5.4	2.5	26.4	38.0	1.60	3.0	16.4	INT0360			
37	1.50	39.8	25.4	3.6	5.5	2.5	27.1	39.0	1.60	3.0	16.8	INT0370			
38	1.50	40.8	26.4	3.7	5.5	2.5	28.2	40.0	1.60	3.0	22.5	INT0380			
39	1.50	42.0	27.2	3.8	5.6	2.5	28.8	41.0	1.60	3.0	26.0	INT0390			
40	1.75	43.6	27.8	3.9	5.6	2.5	44.6	42.5	1.85	3.8	27.0	INT0400			
41	1.75	44.5	28.6	4.0	5.9	2.5	45.0	43.5	1.85	3.8	27.6	INT0410			
42	1.75	45.5	29.6	4.1	5.9	2.5	44.7	44.5	1.85	3.8	28.4	INT0420			
43	1.75	46.6	30.6	4.2	5.9	2.5	44.6	45.5	1.85	3.8	28.8	INT0430			
44	1.75	47.5	31.4	4.2	6.6	2.5	43.5	46.5	1.85	3.4	29.5	INT0440			
45	1.75	48.5	32.0	4.3	6.2	2.5	43.1	47.5	1.85	3.4	30.2	INT0450			
46	1.75	49.5	32.7	4.4	6.3	2.5	42.9	48.5	1.85	3.4	30.6	INT0460			
47	1.75	50.5	33.5	4.4	6.4	2.5	43.5	49.5	1.85	3.4	31.4	INT0470			
48	1.75	51.5	34.5	4.5	6.4	2.5	43.2	50.5	1.85	3.4	32.0	INT0480			
49	2.00	54.2	36.2	4.6	6.5	2.5	68.0	52.0	2.15	4.5	40.5	INT0500			
51	2.00	55.2	37.3	4.7	6.5	2.5	68.2	54.0	2.15	4.5	41.2	INT0510			
52	2.00	56.2	37.6	4.7	6.7	2.5	68.25	55.0	2.15	4.5	42.0	INT0520			
53	2.00	57.2	38.9	4.8	6.7	2.5	68.7	56.0	2.15	4.5	42.9	INT0530			
54	2.00	58.2	39.6	5.0	6.7	2.5	68.4	57.0	2.15	4.5	43.0	INT0540			
55	2.00	60.2	40.7	5.0	6.8	2.5	68.3	58.0	2.15	4.5	44.4	INT0550			
56	2.00	60.2	41.7	5.1	6.8	2.5	68.3	59.5	2.15	4.5	45.2	INT0560			
57	2.00	61.2	42.7	5.1	6.9	2.5	68.6	60.0	2.15	4.5	46.0	INT0570			
58	2.00	62.2	43.0	5.2	6.9	2.5	68.8	61.0	2.15	4.5	46.7	INT0580			
60	2.00	64.7	44.7	5.4	7.3	2.5	61.0	63.0	2.15	4.5	48.3	INT0600			
62	2.00	66.2	46.7	5.6	7.3	2.5	60.6	65.0	2.15	4.5	48.8	INT0620			
63	2.00	67.2	47.7	5.6	7.3	2.5	60.6	66.0	2.15	4.5	50.0	INT0630			
64	2.00	68.2	48.2	5.7	7.5	2.5	60.6	67.0	2.15	4.5	51.4	INT0640			
65	2.50	69.2	49.0	5.8	7.8	3.0	121.0	68.0	2.65	4.5	51.4	INT0650			
67	2.50	71.5	50.8	6.0	7.7	3.0	121.0	70.0	2.65	4.5	52.8	INT0670			
68	2.50	72.5	51.8	6.1	7.8	3.0	121.5	71.5	2.65	4.5	54.8	INT0680			
70	2.50	74.5	53.6	6.2	7.8	3.0	119.0	73.0	2.65	4.5	55.2	INT0700			
72	2.50	76.9	56.6	6.4	7.8	3.0	119.2	75.0	2.65	4.5	64.0	INT0720			
75	2.50	78.9	58.6	6.6	7.8	3.0	119.0	76.0	2.65	4.5	62.0	INT0750			
77	2.50	81.0	60.4	6.7	7.9	3.0	121.1	82.0	2.65	4.5	61.8	INT0770			
78	2.50	82.5	60.1	6.8	8.0	3.0	123.0	81.0	2.65	4.5	62.3	INT0780			
80	2.50	85.0	62.1	7.0	8.0	3.0	123.0	83.5	2.65	5.2	74.6	INT0800			
82	2.50	87.5	64.1	7.0	8.0	3.0	118.0	85.5	2.65	5.2	74.6	INT0820			
85	3.00	90.5	66.9	7.2	8.6	3.5	201.4	86.5	3.15	5.2	78.5	INT0850			
87	3.00	92.5	68.9	7.3	8.6	3.5	204.6	89.5	3.15	5.2	81.3	INT0870			
88	3.00	93.5	69.9	7.4	8.6	3.5	208.4	91.5	3.15	5.2	82.1	INT0880			
90	3.00	95.5	71.9	7.6	8.6	3.5	199.0	93.5	3.15	5.2	84.0	INT0900			
92	3.00	97.5	73.7	7.8	8.7	3.5	201.0	95.5	3.15	5.2	85.6	INT0920			
95	3.00	100.5	76.5	8.1	8.8	3.5	195.0	98.5	3.15	5.2	88.6	INT0950			
97	3.00	102.5	78.5	8.2	8.8	3.5	192.0	100.5	3.15	5.2	90.9	INT0970			
98	3.00	103.5	79.0	8.3	8.9	3.5	191.0	101.5	3.15	5.2	91.3	INT0980			
100	3.00	106.0	80.6	8.4	9.2	3.5	188.0	103.0	3.15	6.2	92.1	INT1000			
102	4.00	108.0	82.0	8.5	9.5	3.5	430.0	106.0	4.15	6.0	106.8	INT1020			
103	4.00	112.0	85.0	8.7	9.5	3.5	436.0	109.0	4.15	6.0	112.0	INT1050			
104	4.00	115.0	88.0	8.9	9.5	3.5	419.0	112.0	4.15	6.0	115.0	INT1080			
110	4.00	117.0	92.2	9.0	10.4	3.5	419.0	114.0	4.15	6.0	117.0	INT1100			
112	4.00	119.0	96.0	9.1	10.5	3.5	489.0	116.0	4.15	6.0	119.0	INT1120			
115	4.00	122.0	99.0	9.3	10.5	3.5	466.0	119.0	4.15	6.0	122.0	INT1150			
120	4.00	127.0	99.9	9.7	11.0	3.5	399.0	124.0	4.15	6.0	127.0	INT1200			